DIGITUS®

*Enjoy connections. Live.*

# DIGITUS Professional KVM-TFT consoles

**DS-76100**
**EAN 4016032258674**

The professionally DIGITUS KVM console offers through his absolute modular construction many of possibly individual applications. The console can be composite for his intended application range. Therefore this console is on the one hand cost-saving as well as upgrade- and rebuildable at every time and warrants a high future-proof.
The console consists out of four main parts which can be ordered separately and comfortable and easy are composed of following elements to match favored control element:
1.The main console, composed of the console-frame with monitor and touchpad
2.The mounting frames for the mounting parts in a cabinet
3.A keyboard
4.A KVM-module
The matching connecting cables for every KVM-module are also available.

**Logistical Information**

| | |
|---|---|
| Packaging Unit (pcs) | 1 |
| Packet weight (kg) | 16.5 |
| Box weight in kg | 16.5 |
| Country of origin | Taiwan |

The main console:
The main console consists of a rugged metal mounting frame, one 43,2cm (17"") or one 48,3cm (19"") TFT-monitor and a built in touchpad.
Prominent features are:
Rugged metal frame
1U construction
Modular capability of connecting for touchpad, keyboard, monitor, mounting frame and KVM-module
Touchpad with simulated scroll-wheel control
Two selectable monitors:
o Monitor 43,2cm (17"), (DS-75100)
Resolution:1280x1024 Pixel at 60/70/75Hz
Active screen area: 337,9x270,3(mm)²
Pixel-Pitch:0,264(H)x0,264(V)(mm)
Brightness: 300(cd/m²)
Contrast:800:1
Maximum angle: ~80°
o Monitor 48,3cm (19"), (DS-76100)
Resolution: 1280x1024 Pixel at 60/70/75Hz
Active screen area: 376,3x301,1(mm)²
Pixel-Pitch:0,294(H)x0,294(V)(mm)
Brightness: 300(cd/m²)
Contrast:800:1
Maximum angle: ~85°
The mounting frame:
Depending on the cabinet installation depth are two several mounting frames selectable:
DS-70100: For cabinet installation depth of 40cm (15"3/4) to 77cm (30" 5/16), Lenght:385mm (15"" 3/20)
DS-70101:For cabinet installation depth of 59cm (23" 7/32) to 96cm (37" 3/4), Length:575mm (22"" 13/20)
Keyboards:
The ergonomical keyboards are manufactured custom-fit for the console and will be connect easily via Mini-USB. Layouts are available for the following countries:

DIGITUS®

*Enjoy connections. Live.*

Germany (DS-70000GE), United Kingdom (DS-70000UK), USA (DS-70000US), France (DS-70000FR), Italy (DS-70000IT), Spain (DS-70000ES), Portugal (DS-70000PT)
More keyboard layouts after request.
The KVM-modules:
Several KVM-modules are available for the console which are close to leave nothing to be desired. The connection uses a built in connector from the console frame to the KVM-module.
Available are six modules with an eight or sixteen KVM-ports and with or without IP access.
DS-11210:Combo-KVM module for USB and PS/2, 1-Port
Direct connection to a server or to an already existing KVM
Video resolution up to 1920x1440 pixels; supports DDC2B
Dimensions (WxDxH): 40x404x114mm; (1.02x15.91x4.49")
DS-11215:Combo-KVM module for USB and PS/2, 1-port, with IP access possibility
Direct connection to a server or to an already existing KVM
TCP/IP access possibility via web browser or VNC client
Own internal firewall and security management functions
Special On-Screen-Display menu
Video resolution up to 1600x1200 pixels at 85Hz
Dimensions (WxDxH): 43x404x220mm; (1.69x15.91x8.66")
DS-13210:Combo-KVM module for USB and PS/2, 8-ports or 16-ports
DS-14210
Direct connection to a server or to an already existing KVM
Auto scan function
Password protection
Special On-Screen-Display menu
Video resolution up to 1920x1440 pixels; supports DDC2B
Dimensions (WxDxH): 40x404x114mm; (1.02x15.91x4.49"
DS-13215:Combo-KVM module for USB and PS/2, 8-ports or 16-ports, with IP access possibility
DS-14215
Direct connection to a server or to an already existing KVM
Auto scan function
Password protection
TCP/IP access possibility via web browser or VNC client
Own internal firewall and security management functions
Special On-Screen-Display menu
Video resolution up to 1600x1200 pixels at 85Hz
Dimensions (WxDxH): 43x404x220mm; 1.69x15.91x8.66")
Cables:
The KVM connection cables are available from 1.8m (6') up to 6.0m (20')
PS/2:DS-19111 (1,8m; 6'), DS-19112(3,0m; 10'), DS-19113(6,0m; 20')
USB:DS-19211 (1,8m; 6'), DS-19212(3,0m; 10'), DS-19213(5,0m; 20')
For more details about the separate components please visit our website

DIGITUS®

*Enjoy connections. Live.*

www.digitus.info.